



Scan QR to visit web page



ARMORTOP OUTDOOR ACRYLIC EPOXY COATING



ArmorTop II is a specialized acrylic coating developed by ArmorPoxy in response to the high demand for outdoor concrete and asphalt coating. **ArmorTop II** works on concrete, cement, bricks, wood, and asphalt. There are eight standard colors to choose from, and the coatings are factory-mixed with fine silica sand for safe, textured playing surfaces.

ArmorTop II is an economical coating designed to resist abrasion, weathering, and moisture degradation. Used extensively at tennis courts, pickle ball courts, balconies, decks, sidewalks, walkways, and theme parks worldwide for appearance issues, ease of cleaning, and safety. Commercial/Industrial grade, not like 'home center' low solids, water-based coatings.

- Ready to use 1 part coating
- Applied with a soft rubber squeegee
- 2 coats recommended
- Application temperature above 50°F for at least 24 hours
- Stir before using
- Coverage is .12 to .15 gallon per square yard per coat (60-75 sq ft per gallon per coat)
- Drying time is 30 to 60 minutes
- Allow 48 hours before foot traffic
- Light vehicle rated

Color Chart ArmorTop




Light Green



Medium Green




Dark Green



Light Brown



Red



Brown



Gray



Blue



Burgundy

1260 North Ave,
Plainfield, NJ 07062

www.armorpoxy.com

1-888-755-7361