



ARMPP1PT
1-PART EPOXY PAINT

PRODUCT DESCRIPTION

Armorpoxy's 1-Part Epoxy Pool Paint is an excellent choice to recoat previously painted chlorinated rubber and synthetic rubber painted pools, specifically in VOC restricted areas. For compatibility purposes, the existing paint on a previously painted surface should be determined before painting. Aged plaster should be checked for integrity. Check for hollow or weak/crumbling plaster by using a ball-peen hammer or any other comparable method. Perform repairs to the plaster before painting. Can be applied over most types of epoxy pool coatings in good condition, as well as bare concrete, plaster, gunite and fiberglass. Can be used in jacuzzi's and hot tubs. Dries quickly, durable, and resists fading, blistering, chemicals and abrasion

PRODUCT FEATURES

- Can be applied over most types of epoxy pool coatings
- Easy prep with power wash and acid etch
- No primer required
- Satin finish
- Can be applied using a 3/8" roller
- Multiple coats can be applied

PRODUCTS TO BE USED WITH

N/A

**NOTE: NOT FOR USE ON BARE FIBERGLASS/GELCOATS.
DO NOT USE IN HOT TUBS OR SPAS.**

PHYSICAL PROPERTIES

VEHICLE TYPE	Synthetic Rubber
FINISH	Gloss
COMPONENTS	1
MIX RATIO	Self-priming. Mechanically mix the paint to achieve uniform consistency
CURING MECHANISM	Air Dry
SOLIDS BY VOLUME	43% ± 1%
SOLIDS BY WEIGHT	55% ± 1%
COVERAGE	Coverage will depend on porosity and texture of the surface. Up to 400 sq ft/gal/coat on previously painted synthetic or chlorinated rubber surfaces.
VOC	325 g/l max (as supplied)
FLASH POINT	103° F (SETA)
APPLICATION METHOD:	Brush, no thicker than 3/8" Mohair or Lambskin Roller,
DRY FILM THICKNESS PER COAT	1.0 mils (2.3 mils wet)
NUMBER OF COATS	2 (product is self-priming)
APPLICATION TEMP.	50°F min/90°F max
RECOAT TIME	Min. overnight to 24 hours. After 72 hours, must sand before applying 2nd coat.
DRY TIME	Outdoor Pool: 5-7 days before filling Indoor Pool: 10-14 days before filling. Use adequate ventilation.

BENEFITS



**Works on
most pool surfaces**



1-Part Product



Roll on Application

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.