

# ARMULWAGLCO

## ULTRAGLAZE CLEAR TOPCOAT

### PRODUCT DESCRIPTION

Ultraglaze is an amazing 'water clear' (no amber/yellow cast like many clear coats) that can be used over most any surface. Perfect for topcoating our regular ArmorPoxy, and most other coatings to add significant life and shine. Can also be made less slippery by the addition of our Armorgrip Non Skid additive. Please note that Ultraglaze is not highly resistant to fuels and solvents.

### RECOMMENED SURFACES

- Garage Floors
- Patios
- Porches
- Brick
- Stone
- Driveways
- Exposed Aggregate
- Stamped Concrete

### PRODUCTS TO BE USED WITH

- ArmorClad Coating Kit
- Virtually any other ArmorPoxy epoxy coating

### FEATURES

- Seals and protects painted, stained or bare concrete
- Seals in color
- Reduces pockmarking and cracking
- Clear finish, will not yellow
- Premium, urethane-fortified acrylic formula

### PHYSICAL PROPERTIES

Resin Type	Water-based acrylic urethane
Pigment Type	none
Visual appearance	Milky white (wet); dries clear
Tire marking	Resistant to most tires
Clean-up	Soap and Water
Shelf life	2 years min. (closed container)
Gloss	25 (1 coat)
Gloss retention	Excellent
Ultraviolet resistance	Excellent
Dry Times (77°F (25°C) 50% RH)	--
Touch	15 minutes
Recoat	2 hours
Light Foot Traffic	24 hours
Vehicle Traffic	72 hours
Konig hardness	64
VOC	< 250 g/L
Odor	Low
Coverage	up to 700 sq.ft per gallon. will vary dependt on surfsce

### CHEMICAL RESISTANCE

ASTM D-1308

Gasoline	resistant
Water	resistant
Oil	resistant
Salt	resistant
Chlorine	resistant

### BENEFITS




Resistant to Hot Tire Pickup



Gloss Finish



2 Year Shelf Life



UV Resistant



Ready for Use in 24 Hours



Easy to Clean and Maintain

**LIMITED WARRANTY:** Manufacturer/Seller makes no warranty of any kind except that this product is free from defect and is of merchantable quality. Buyer remedy for breach of warranty is limited to replacement of ArmorPoxy product or refund of purchase price. Convenience Products will not be responsible for labor or the cost of labor for removal or application of any product. The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.