

ARMAS

ARMOR SHIELD - HYBRID POLYURETHANE SEALER

PRODUCT DESCRIPTION

Armor Shield is an advanced single component water-based polyurethane hybrid sealer. This sealer can be used as a standalone product when applied in multiple coats or in conjunction with our Armor Liquid Membrane coating as a topcoat. Armor Shield is UV stable and can be used for residential and commercial use both indoors and outdoors. It outperforms polyurea, acrylic and urethane based sealers and can withstand foot traffic and vehicular traffic. It is resistant to chemicals, household cleaners, and other common fluid cleaners. It can be applied by brush or roller. 3 coat minimum can be accomplished in a single day with it's super fast drying time.

SUBSTRATES

Works on concrete, pavers, driveways, polished concrete, masonry, pool decks, and shower floors.

FEATURES / BENEFITS

UV Resistant, Self-Priming, Odorless, Enhances substrate color, Can withstand foot and/or vehicle traffic

APPLICATION AND SPECIFICATIONS

APPLICATION	AIRLESS SPRAYER, TIP SIZE 17, 1/2" WOVEN SHORT NAP ROLLER OR MAGIC TROWEL
APPLICATION ENVIRONMENT	APPLY AT TEMPERATURES FROM 50°F TO 90°F
COLOR	WHITE/MILKY LIQUID
CHEMICAL TYPE	POLYURETHANE HYBRID
CLEAN UP	WATER
SHelf LIFE	1 YEAR (AMBIENT TEMPERATURE OF 60F - 72F)
PACKAGING	1 GALLON, 5 GALLONS
COLORS AVAILABLE	CLEAR, LT. GRAY, MED GRAY, WHITE, LT BROWN, DARK BROWN, BEIGE, BLACK, GREEN, CREAM


DRY TIMES

45°F	90 MINUTES
60°F	60 MINUTES
72°F	20 MINUTES
80°F	15 MINUTES
100°F	10-12 MINUTES

COVERAGE (SF per gallon of mixture, 3 coats @ 20 mils Total thickness)

150 - 300 SF	YIELD PER GALLON MAY VARY DEPENDING ON SUBSTRATE AND FLOOR POROSITY
--------------	---

ADVANTAGES



UV Stable



Gloss Finish



Quick Drying




Can withstand Vehicle Traffic



Eco-Friendly

APPLICATIONS




Pavers and Driveways



Commercial and Industrial Facilities



Garages



Tiles
(Pebble, Slate, Stone, and many more!)



Basements

PRECAUTIONS

Always test a small area first to determine ease of application and desired results. Gloves and eye protection should be worn during application. Do not mix with other cleaners. Not for use on humans or animals. If any contact with skin or eyes occurs, wash immediately with plenty of water. Be sure to read container label and Material Safety Data Sheet before using this product.

LIMITED WARRANTY NOTICE

ArmorPoxy warrants that its products will meet their specifications. There are no other warranties, expressed or implied of merchantability or fitness of use. The only obligation of the seller-manufacturer shall be to replace material found to be defective. ArmorPoxy will not be liable for labor or consequential damage of any kind. The information contained herein is, to the best of our knowledge and belief, true and accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state and local laws and regulations. All chemicals may present unknown health hazards and should be used with caution.